BENLEES

Hydraulic Shower Hinge Selection Guide

Choose by installation type | Hydraulic soft-close (final 20°)



G-90 Wall-to-glass



B-90 Wall-to-glass




BL-180 Glass-to-glass



W-180 Glass-to-glass

Model	Installation	Glass	Automatic closing	Adjustment
G-90	Wall-to-glass	8–12 mm	From 85° to 0°	Adjustable closing speed
B-90	Wall-to-glass	8–12 mm	From 85° to 0°	3-level closing force (also affects closing speed)
BL-180	Glass-to-glass	8–12 mm	From 85° to 0°	Adjustable closing speed
W-180	Glass-to-glass	8–12 mm	From 85° to 0°	Adjustable closing speed



Angle zones (all four models)

- **Hold-open 85–90°**
- **Self-closing 85–0°**
- **Soft-close 20–0°**

Max door weight 45–60 kg — use 2 or 3 hinges per door depending on size and weight.
Material: G-90 / B-90 / BL-180: 304 stainless steel (main material). W-180: stainless steel.
Optional finishes: Brushed (satin) · Polished · Rose gold / Gold · Powder-coated black. Availability varies by model.

Send us your door size and glass weight — we'll recommend the right hinge set.

Baifeili Precision Manufacturing Co., Ltd.
WhatsApp: +86 153 0289 6550
Email: jiajinli058@gmail.com

WhatsApp